Acrylic

PLASTIC & POLYCARBONATE

CHEMCAST# Translucency

ACRYLIC

Acrylic is available for the sign industry in three different types. Call for more detailed information on which technology best fits your needs.

Extruded Acrylic

Acrylite FF

Acrylite FF sheet is a rigid, impact-resistant, weatherable, light weight thermoplastic that offers excellent optical quality. Half the weight of glass with many times the impact resistance. Can be easily cut, routed, drilled, and cemented.



Extruded Acrylic

PERSPEX

This acrylic sheet is ideal for applications where a non-glare surface is required. ADA, picture framing, directories and indoor reflective light areas. Cuts, forms and fabricates easily. Clear sheets only.

Size	Thickness	Stock#
4'X6'	.060"	NGCH1M
4'X8'	.125"	NGCN2M

COLOR	CTRO#	CHEWICAST#	Translucency
WHITE	015-2	7328	
WHITE	020-4	2447	1
WHITE	048-2	7420	ĺ
WHITE	051-6	2067	ĺ
WHITE	054-3	7138	1
AQUA	552-1	2324	1
BLUE	605-0	2114	1
BLUE	606-0	2050	1
BLUE	607-1	2051	1
BLUE	6109-0	2648	T
GREEN	506-0	2030	Translucent
GREEN	507-0	2108	1
IVORY	047-2	2146	1
ORANGE	303-0	2119	1
RED	205-0	2157	1
RED	209-0	2415	
RED	211-1	2283	1
RED	278-0	2793	
YELLOW	406-1	2016	
YELLOW	407-2	2037	
BRONZE	131-2	2412	
BRONZE	126-4	2404	1
BRONZE	145-5	2539	1
BRONZE	311-1	2370	1
GRAY	103-2	2064	1
GRAY	104-1	2074	1
GRAY	141-5	2514	1
GRAY	142-1	2538	Transparent
GRAY	144-7	2515	
AMBER	436-4	2422	
BLUE	625-5	2069	1
BLUE	668-0	2424	1
GREEN	545-2	2092	1
RED	257-0	2426	1
YELLOW	430-7	2208	1
WHITE	076-0	7508	
BLACK	199-0	2025	Opaque
BROWN	324-2	2418	1

CAST ACRYLIC CROSS REFERENCE CHART

CYRO#

COLOR

Т

Do not combine different brands in the same sign

Impact Modified Acrylic

Acrylite SG Sheet

Developed specifically for the sign industry, Acrylite SG acrylic sheet combines light weight and high optical quality with outstanding ease of fabrication, impact strength, superior color consistency and weatherability. Ideal for use in channel letters, formed letters, and shapes as well as



back-painted signs, Resists chipping and melting. Cutting, routing, drilling, forming and cementing can be performed. Offers the look of acrylic with

the impact strength required for fabrication, handling, shipping and sign installation.

SG now available on reels. (Each reel represents a full pallet of sheets)

Colors: White, black, yellow, blue, and three shades of red.

Thicknesses: .118 & .177

Sizes: 4'X8', 4'X10', 6'X8', and 6'X10'

Tuf-Glas Coil

Tuf-Glas is available in Clear and Colors by special order

Tuf-Glas offers the clarity and stiffness associated with acrylics combined with toughness at least seven times tougher than standard acrylic. Conventional solvent cements will join Tuf-Glas.

Standard sign paints such as Grip-Flex and Lacryl can be used to decorate the surfaces. Cutting can be done with power sawing equip-



ment with blades from 4 to 8 teeth per inch, bands saws from 10 to 14 teeth.

All edges are trimmed and the sheet is masked with a poly coating so it gets to you in good condition. Stocked in coils for your convenience. Sold in 1 linear foot increments from the coil. (Clear available)

Width	Thickness	Stock#
52"	.177	187X52WTG
76"	.177	187X76WTG
100"	.177	187X100WTG



PLASTIC & POLYCARBONATE

Cell Cast Acrylic Sheets

Cast acrylic sheets are made to exacting standards. Half the weight of glass with many times the impact resistance. Offers excellent optical characteristics, thickness tolerances, light stability, and low internal stress levels for consistent performance. Weatherable and can be easily cut, sawed, machined, thermoformed and cemented. In addition to colorless sheet, a wide range of transparent and translucent colors are available. Custom colors can be by special order by special order by special order.

Acrylite GP



Thicknesses: .118", .177", .236", .354", .472", .708", .944" Sizes: 4'X6', 4'X8', 4'X10', 5'X8', 5'X10', 6'X8', 6'X10' Chemcast



Thicknesses: .118", .177", .236", .354", .472", .708", .944" Sizes: 51"X100" & 6'X8'

Polycarbonate

White Spartec

This all-polycarbonate weatherable sheet combines the impact strength of general purpose polycarbonate with oustanding UV stability. Sungard is highly resistant to weathering, discoloration, surface haze, loss of impact strength or other properties after prolonged outdoor exposure. 12 year limited warranty. Sold by the liner foot.





Width	Thickness	Stock#
76"	.177	WSG76177
104"	.177	WSG100177

Clear also available. Call for information.

Clear GE Lexan

SGC-100

SGC100 (Solar Grade) sheet for signs combines the impact strength of Lexan polycarbonate sheet with a proprietary UVresistant caplayer. It is used in a variety of thermoformed and flat signs, whether screen-printed, painted or decorated with vinyl graphics.




Providing long-lasting clarity over a wide range of environments, Lexan SGC100 sheet offers extended service life and reduced life-cycle material costs over acrylic. Backed by a 10-year limited warranty against yellowing, loss of light transmission and breakage. Sold by the linear inch from the coil.

Width	Thickness	Stock#	
51"	.118	S10451118	
52"	.150	S10452150	
64"	.150	S10464150	
75"	.150	S10475150	
99"	.177	S10499177	
100"	.177	S104100177	
52"	.150	SGC10052150	UV Coated
64"	.150	SGC10064150	UV Coated
76"	.150	SGC10076150	UV Coated
76"	.177	SGC10076177	UV Coated
100"	.125	SGC100100125	UV Coated
100"	.177	SGC100100177	UV Coated

White GE Lexan

Lexan SG404 sheet is a pigmented, UV-resistant, solar-grade sheet for signs offering excellent aesthetics, high impact strength and a 5 year limited warranty against breakage. Easily fabricated and maintained. Six colors available for special order by the roll.





Corrugated STA-TUF

An impact-resistant thermoplastic alloy. It offers good weatherablility and light transmission and is solventcementable. Comes in a "V" shaped corrugatation. Most standard uses are for reader-board fabrication. Fast turnaround special order.

.070" Thick sign white

Size	Stock#
120" X 48-1/4"	STV3600H3
144" X 48-1/4"	STV3600H4

Yellow and Ivory also available





1"

V-3

SG-404